2023 PARAFFIN WAX



REACH Ref. No.: 01-2119488076-30-XXXX

IRAWAX® 3





IRAWAX® 3 is a semi-refined paraffin wax with oil content between 3 to 5%. In comparison with IRAWAX® 1, it has higher oil content while other physical specification is the same. It is a perfect choice for different industries such as candle making companies, paint and wax companies and many other industries. This product is available in carton with shrink or PP bag based on customer preference.

| BRAND | IRAWAX® | |
|---------------------|--------------------|--|
| PRODUCT CODE | PWCB102 | |
| TRADE NAME | PARAFFIN WAX | |
| GRADE | SEMI-REFINED | |
| ORIGIN | MIDDLE EAST | |
| HS CODE | 2712.20.90.00 | |
| PACKING | EUR-Pallet/ Carton | |
| OPTIONAL PACKING | PP BAG | |
| SHAPE | SLABS | |
| NO. OF SLABS IN CTN | 4 - 5 | |
| GROSS WEIGHT | 25 KG ± 3% | |
| NET WEIGHT | 24.5 KG ± 3% | |

| SPECIFICATION | VALUE | METHOD |
|--------------------------------|-------------|------------|
| OIL CONTENT (%) | 4 ± 1 | ASTM D721 |
| FORM | SOLID | - |
| COLOR | < 0.5 | IP 17 |
| ODOR | Odorless | - |
| MELTING POINT | 60 - 65 | ASTM D87 |
| KINEMATIC VISCOSITIES @ 100 °C | 6 - 7 | ASTM D445 |
| DENSITIES @ 100 °C | 860 - 870 | ASTM D1298 |
| FLASH POINT | MIN 220 ℃ | ASTM D92 |
| PENETRATION | MAX 30 MM/S | ASTM D937 |
| CONGEALING POINT | 60 ℃ | ASTM D938 |

ALL PICTURES SHOWN ARE FOR ILLUSTRATION PURPOSE ONLY. ACTUAL PRODUCT MAY VARY DUE TO PRODUCT ENHANCEMENT.